

AIC Nightly Fixture Schedule

Type	Catalog	Manufacturer	Description	Mounting Notes
A	JU-R FL L1 35 24 SS + AS	Targetti	Targetti Jupiter 3". Cylindrical inground unit, uplighting the chest of the lions. Asymmetrical screen and flood lens, 3500K color temp. Brushed natural finish.	Inground mounting in the sidewalk.
B	KPLM 41 WW L1 30 + 1E2525 1DU2521	Targetti	Targetti Keplero Mini Wall Wash 6". Cylindrical inground unit, uplighting the walls of the entrance. 3000K color temp. Brushed natural finish.	Inground mounting in the sidewalk.
C	KPLM RP FL L1 RGBW + 1E2525 1DU2521	Targetti	Targetti Keplero Mini RGBW 6". Cylindrical inground unit, uplighting the planters. RGBW with flood lens. Brushed natural finish.	Inground mounting in the sidewalk.
D	JM R SP L1 30 24 SS + AS	Targetti	Targetti Jupiter Mini 2". Cylindrical inground unit uplighting the arches of the entrance. Asymmetrical screen and spot lens, 3000K color temp. Brushed natural finish.	Inground mounting in the sidewalk.
E	JE R 10 WW 48 40 E LV + 1US2751	Targetti	Targetti Jedi Recessed 48". Linear ingrade unit, uplighting the wall behind the posters. Wall washer lens, 4000K color temp. Brushed natural finish.	Inground mounting in front of the wall.
F	N 139-2040 LED-6/24W-RGBW 1645.3 29 20 9.45	We-Ef	We-Ef FLC220 LED Color Changer Floodlight 7.48". RGBW Floodlight projector, uplighting the columns and the ornaments. Symmetric, narrow beam, white finish.	147-0023 Floodlight mounting bracket, mounted on the sides of the columns and ornaments.
G	M 139-1913 LED-12/48W-RGBW 3204.9 50 20 17.00	We-Ef	We-Ef FLC230 LED Color Changer Floodlight 10.24". RGBW Floodlight projector, lighting the posters. Symmetric, medium beam, white finish.	147-00296 Floodlight mounting bracket, mounted on the sides of the posters.
H1	LLI-LCCW7.6W-68-R52-24V-90	LLI Architectural Lighting	Tight Pitch Color Changing LED RGBW Tapelight - IP68. R52, 5200K, color option. 7.6w. Uplighting the frieze.	Mounted with H2 Architectural extrusion and angled mounting clip.
H2	LLI-XS-ANG-WH-F-94IN	LLI Architectural Lighting	Angled Extrusion. White finish with frosted lens in 94" sections.	Mounted just below the script, using the angles mounting clip.
I1	LLI-LTP5.9W-65-52K-24V-90	LLI Architectural Lighting	Tight Pitch 5.9W 90+CRI LED Tapelight IP65. 5200K color temp. Uplighting the dentils.	Mounted with I2 Architectural extrusion.
I2	LLI-XS-THN-WH-F-94IN	LLI Architectural Lighting	Thin Extrusion. White finish with frosted lens in 94" sections.	Mounted on the ledge beneath the dentils with standard mounting clip.
J1	LLI-LTW5.3W-68-2K5-24V-90	LLI Architectural Lighting	Tunable White 5.3W LED Tapelight IP68. 2700K-5200K color temp range. Uplighting the recesses, medallions, and reliefs.	Recesses mounted with J2 Custom Extrusion. Medallions mounted with J3 Custom Extrusion. Reliefs mounted with J4 Custom Extrusion.
J2	N/A	aspectLED	Custom Aluminum Extrusions. 2.5' aluminum extrusion, painted to match the limestone. White frosted lens, end connection, IP68 rating.	Mounted just below the recesses with standard mounting clip.
J3	N/A	aspectLED	Custom Aluminum Extrusions. 1' aluminum extrusion, painted to match the limestone. White frosted lens, end connection, IP68 rating.	Mounted just below the medallions with standard mounting clip.
J4	N/A	aspectLED	Custom Aluminum Extrusions. 3' aluminum extrusion, painted to match the limestone. White frosted lens, end connection, IP68 rating.	Mounted just below the reliefs with standard mounting clip.

K	LULS 40K 40 120 MS 24	Wagner	Lumenrail Linear Symmetric. 4000K color temp, 40w LED light, downlighting the steps on the handrails. Matte symmetric lens. 120° spread.	Mounted on the underside of the handrails.
---	-----------------------	--------	--	--

AIC Event Lighting Fixture Schedule

Type	Catalog	Manufacturer	Description	Mounting Notes
EA	N/A	Chauvet	Maverick MK3 Profile. Powerful, 90+ CRI, LED profile moving head for lighting the wall and cross lighting the steps. Shutters, and multiple gobo wheels. Must include Edison to Powerkon power cable and mounting feet.	Floor mounted.
EB	N/A	Chauvet	Ovation E-930VW. LED Ellipsoidal fixture, area lighting for limos and steps. 90+ CRI, +/- green, variable color temperature. Must include 50° barrel, standard truss clamp, and Powerkon power cable.	Mounted on truss structures.
EC	N/A	Chauvet	COLORado 3 Solo. LED Wash fixture, uplighting for sides of building. Must include Powerkon power cable.	Floor mounts.
ED	405-B, 400PH-G	ETC	ETC Source4 5°. 750w fixture with glass gobos for projection of the logos and symbols. Must include glass gobo holders, standard truss clamps and 2P&G power cable.	Mounted on truss structures.